

# Shenzhen JZD Wires & Cables Co.,Ltd

ADD:Building C, Liansheng Industrial Park, No.77 Yanshan Avenue, Baoan District, Shenzhen City

TEL : 0086 13510784550

E-mail : shenzhen@jzdcable.com

## 300/500V Multi Core Copper PVC Insulated and Sheathed Flexible Cable with Shield

Voltage Level (V)	Nominal section (mm <sup>2</sup> )	Insulation thickness (mm)	Sheath thickness (mm)	Reference overall diameter (mm)	Reference weight (KG,KM)	Maximum resistance of conductor at 20°C
300/500	2x0.2	0.4	0.6	4.71	21.19	92.3
	2x0.3	0.5	0.6	5.41	35.04	69.2
	2x0.4	0.5	0.6	5.68	41.09	48.2
	2x0.5	0.5	0.6	5.84	44.64	39.0
	2x0.75	0.5	0.6	6.24	52.65	26.0
	2x1.0	0.6	0.6	7.03	64.25	19.5
	2x1.5	0.6	0.8	7.99	87.51	13.3
	2x2.5	0.7	1.0	9.63	125.25	8.0
	2x4	0.8	1.2	11.84	197.93	5.0
	3x0.12	0.4	0.6	4.63	20.53	158.0
	3x0.2	0.4	0.6	5.05	30.40	92.3
	3x0.3	0.5	0.6	5.67	38.40	69.2
	3x0.4	0.5	0.6	5.96	45.00	48.2
	3x0.5	0.5	0.6	6.14	50.60	39.0
	3x0.75	0.5	0.6	6.57	55.50	26.0
	3x1	0.5	0.8	8.9	70.25	19.5
	3x1.5	0.6	0.8	9.8	93.00	13.3